

AUTO LIGHTER / PHOTOCELL SWITCH

		
CA-11003 (AC110V, 3A) CA-22003 (AC220V, 3A)	CB-11003 (AC110V, 3A) CB-22003 (AC220V, 3A)	TOP-11003 (AC110V, 3A) TOP-22003 (AC220V, 3A)
CA-11006 (AC110V, 6A) CA-22006 (AC220V, 6A)	Cb11006 (AC110V, 6A) CB-22006 (AC220V, 6A)	TOP-11006 (AC110V, 6A) TOP-22006 (AC220V, 6A)
		
CA-11010 (AC110V, 10A) CA-22010 (AC220V, 10A)	CA-11020 (AC110V, 20A) CA-22020 (AC220V, 20A)	CA-22020T (AC220V, 20A) Auto-extinguisher attaches with time switch-specialized for advertisement.
CA-11015 (AC110V, 15A) CA-22015 (AC220V, 15A)		

(1) Standard lighting: 31.5-125 LUX.

(Under conditions at rated voltage and surroundings temperature 20°C.)

(2) Standard unlighting: Below 5 times of lighting

(Under conditions at rated voltage and surroundings temperature 20°C)

(3) Suitable surroundings temperature range: -10°C~+40°C.

(4) Service life time: more than 2,000 times.

(Operational condition: rated voltage, surroundings temperature 20°C)

Operational frequency: 6 Time/Hour.

Diagram of Interior Circuit

